



MARINE CAST STEEL STRAIGHT GLOBE VALVE - 5kg/cm ² (F7311)							
ΔΙΑΣΤΑΣΗ	ΑΠΟΣΤΑΣΗ ΦΛΑΝΤΖΩΝ (L)	ΦΛΑΝΤΖΑ			ΥΨΟΣ (H)	ΒΑΡΟΣ (kg)	ΤΙΜΗ €
		ΕΞΩΤ. Ø	PCD	ΩΠΕΣ			
DN 50	210	130	105	4 x 15	270	15,5	314,00
DN 65	250	155	130	4 x 15	300	25,8	454,00
DN 80	280	180	145	4 x 19	310	32,3	582,00
DN 100	340	200	165	8 x 19	360	47,6	873,00
DN 125	410	235	200	8 x 19	390	71,3	1.222,00
DN 150	480	265	230	8 x 19	445	86	1.207,00
DN 200	570	320	280	8 x 23	530	147	2.710,00
DN 250	740	385	345	12 x 23	791	230	-
DN 300	840	430	390	12 x 23	929	309	-



MARINE CAST STEEL ANGLE GLOBE VALVE - 5kg/cm ² (F7312)							
ΔΙΑΣΤΑΣΗ	ΑΠΟΣΤΑΣΗ ΦΛΑΝΤΖΩΝ (L)	ΦΛΑΝΤΖΑ			ΥΨΟΣ (H)	ΒΑΡΟΣ (kg)	ΤΙΜΗ €
		ΕΞΩΤ. Ø	PCD	ΩΠΕΣ			
DN 50	100	130	105	4 x 15	240	13,3	280,00
DN 65	115	155	130	4 x 15	255	19,5	393,00
DN 80	130	180	145	4 x 19	265	25,5	494,00
DN 100	150	200	165	8 x 19	310	34,8	714,00
DN 125	170	235	200	8 x 19	330	46,5	911,00
DN 150	190	265	230	8 x 19	380	66,5	1.331,00
DN 200	220	320	280	8 x 23	450	111	1.950,00
DN 250	275	385	345	12 x 23	641	178	-
DN 300	310	430	390	12 x 23	748	275	-



MARINE CAST STEEL STRAIGHT GLOBE VALVE - 10kg/cm ² (F7319)							
ΔΙΑΣΤΑΣΗ	ΑΠΟΣΤΑΣΗ ΦΛΑΝΤΖΩΝ (L)	ΦΛΑΝΤΖΑ			ΥΨΟΣ (H)	ΒΑΡΟΣ (kg)	ΤΙΜΗ €
		ΕΞΩΤ. Ø	PCD	ΩΠΕΣ			
DN 50	220	155	120	4 x 19	285	19,9	340,00
DN 65	270	175	140	4 x 19	310	28,7	422,00
DN 80	300	185	150	8 x 19	320	32,4	504,00
DN 100	350	210	175	8 x 19	370	48,7	695,00
DN 125	420	250	210	8 x 23	420	73,1	1.027,00
DN 150	490	280	240	8 x 23	470	104	1.366,00
DN 200	570	330	290	12 x 23	555	162	2.430,00
DN 250	220	155	120	4 x 19	285	304	-
DN 300	270	175	140	4 x 19	310	458	-



MARINE CAST STEEL ANGLE GLOBE VALVE - 10kg/cm ² (F7320)							
ΔΙΑΣΤΑΣΗ	ΑΠΟΣΤΑΣΗ ΦΛΑΝΤΖΩΝ (L)	ΦΛΑΝΤΖΑ			ΥΨΟΣ (H)	ΒΑΡΟΣ (kg)	ΤΙΜΗ €
		ΕΞΩΤ. Ø	PCD	ΩΠΕΣ			
DN 50	120	155	120	4 x 19	240	16,3	293,00
DN 65	130	175	140	4 x 19	260	23,0	378,00
DN 80	140	185	150	8 x 19	265	25,3	449,00
DN 100	160	210	175	8 x 19	300	37,0	605,00
DN 125	180	250	210	8 x 23	350	57,1	950,00
DN 150	205	280	240	8 x 23	400	77,2	1.330,00
DN 200	230	330	290	12 x 23	480	116,0	-
DN 250	290	400	355	12 x 25	680	188,0	-
DN 300	320	445	400	16 x 25	770	256,0	-